

furka plus

7064.01 - 7064.44



binder

upholstery

03

vinyl

description

matt shimmer uni-coloured with fine grain

composition

vinyl coat on a cotton/polyester backing

width

± 137-140 cm, ± 54-55 inches

weight

backing: ± 110 gr/m², ± 5 oz/yd¹

coating: ± 690 gr/m², ± 31 oz/yd¹

thickness

1.1 mm, 0.04 inches

flame retardancy

EN 1021/1-2

BS 5852, crib 5

NF P 92/503 – 507, M2

NF D60-013 (AM 18)

DIN 4102, B2

UNI 9175, classe 1 IM

Cal TB 117

NFPA 260, class 1

IMO 2010 FTP part 8

abrasion

ISO 12947-2

> 300.000 rubs martindale

ASTM D4157

100.000 double rubs wyzenbeek

colorfastness to crocking

ISO 105-X12

wet 5 / dry 5 (scale 1-5)

AATCC 8

wet 5 / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

7 (scale 1-8)

ASTM D4329: 150 hours

4 (scale 1-5)

resistance to blood, urine, sweat and sebum

EN 12720

5 (scale 1-5)

breaking strength

ISO 1421

length 470 N / width 313 N

ASTM D2261

length 7 lbs / width 9 lbs

flexibility

ISO 7854

400.000 cycles

adhesion to coating


ASTM D751

length 8 lbf / width 5 lbf



furka plus


7064.01 - 7064.44



7064.01



7064.02



7064.03



7064.04



7064.05



7064.06



7064.07




7064.08



7064.09




7064.10



7064.11




7064.12



7064.13



7064.14



7064.15




7064.16



7064.17




7064.18



7064.19



7064.20




7064.21



7064.22




7064.23




7064.24



7064.25




7064.26




7064.27




7064.28




7064.29




7064.30



7064.31



7064.32



7064.33



7064.34




7064.35




7064.36




7064.37



7064.38




7064.39




7064.40




7064.41



7064.42



7064.43



7064.44